

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 10W-60

## EUROPEAN FORMULA

PRODUCT # 10248, 10231

### TEST

### ASTM

### TYPICAL

API Gravity	D-1298	33.65
Specific Gravity @ 60°F	D-1298	0.862
Density @ 60°F, lb/gal	D-1298	7.19
CCS @ -25°C, CPS	D-5293	7,000 Max
MRV @ -30°C, CPS	D-4684	60,000 Max
Zinc, WT%	X-ray	0.085
TBN, Mg KOH/g	D-2896	7.5
Viscosity @ 40°C cSt	D-445	211
Viscosity @ 100°C cSt	D-445	25
Viscosity Index	D-2270	149
Flash Point, COC °F	D-92	425
Color		Light Brown

Lucas Synthetic SAE 10W-60 Motor Oil is especially formulated for high mileage or high performance engines; it is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas Synthetic SAE 10W-60 Motor Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

Lucas Synthetic SAE 10W-60 Motor Oil is the perfect lubricant for high RPM and high temperature engines. The exclusive additive package in Lucas Synthetic SAE 10W-60 Motor Oil allows for extended drain intervals.

Lucas Synthetic SAE 10W-60 Motor Oil far exceeds all OEM specifications. Formulated to meet ALL motor that calls for a Synthetic SAE 10W-60 motor oil.

Meets or exceeds American and European OEM specifications API SM/SL/SJ/CF, ACEA A5/B5-04, A3/B4-04, C2-08, C3-07, C2-04, MB 229.31, MB 229.51, VW 50200, 50500, 50501, BMW Longlife-04, Porsche, Ford WSS M2 C 917 A. Suitable for use where VW 50700 is recommended.