

	Selenia Turbo Diesel	Liqui Moly MoS2 Leichtlauf	Liqui Moly Super Leichtlauf	Castrol Magnetec Profession A3	Bardahl XTC	Mobil Super 2000xl	Mobil Delvac XHP	Motul 6100 Synergie	Royal Purple	Total Quartz 7000	Repsol GTI/TD	ENI i-Sint	SHELL Rimula Signia Diesel	SHELL Helix HX7
SAE class	10W-40	10W-40	10W-40	10W-40	10W-40	10W-40	10W-40	10W-40	10W-40	10W40	10W40	10W40	10W40	10W-40
ACEA	B3	B3/B4	B3/B4	B4	B4	B3	B3	B4	B3	B4		B4	E4/E6	B3/B4
Visc. Index	155	164	153	155	156	153	152	153	161	160	>140	158	162	
Viscosity 40°		88.0	93.7	93.1	89.8	97	90.6	102.5	82.5	96.8	97	92	82.0	92.1
Viscosity 100°	14.8	14.0	14.0	14.1	13.8	14.4	13.6	15.0	13.2	14.81	14.4	14.1	13.0	14.4
Viscosity -35°														
Ht/Hs Visc150°		>3.5	>3.5				3.8	3.6						
Pour point	-27°C	-36°C	-36°C	-33°C	-39°C	-30°C	-36°C	-36°C		-24°C	-39°C	-27°C	-36°C	-45°C
Flash point	210°C	230°C	232°C	201°C	200°C	230°C	236°C	228°C	210°C	232°C	215°C	224°C	251°C	246°C
Density15/20°	0.87	0.86	0.87	0.86	0.86	0.87	0.85	0.86		0.87	0.87	0.86	0.85	0.88
TBN	7.4	9.0	10.8		10.7		13	10.4	11.4		10		9.5	
Sulfate ash		1.0	1.0	0.98		0.91	1.0						0.85	