

	<u>Selenia</u> WR	<u>Bardahl</u> XTC C60	<u>Eni</u> iSint	<u>Total</u> Synthetic	<u>Liqui</u> <u>Moly</u> <u>TopTec</u> 4100	<u>Liqui</u> <u>Moly</u> <u>Synthoil</u> <u>High</u> <u>Tech</u>	<u>Castrol</u> <u>Edge</u> <u>Turbo</u> <u>Diesel</u>	<u>Castrol</u> <u>Magnatec</u> <u>Diesel</u> <u>dpf</u>	<u>Mobil</u> <u>Super</u> <u>3000 X1</u>	<u>Mobil</u> <u>Delvac1</u>	<u>Motul</u> <u>8100 x-</u> <u>clean</u>	<u>Motul</u> <u>8100 x-</u> <u>cess</u>	<u>Royal</u> <u>Purple</u>	<u>Shell</u> <u>Helix</u> <u>HX8</u>	<u>Shell</u> <u>Helix</u> <u>Ultra</u>
<u>SAE class</u>	5W-40	5W-40	5W40	5W40	5W-40	5W-40	5W-40	5W-40	5W40	5W40	5W-40	5W-40	5W-40	5W40	5W-40
<u>ACEA</u>	B3/B4	B4	B4	B4	B4/C3	B4	C3	C3	B3/B4	E3/E5	B4/C3	B4	B3/B4	B3/B4	B4
<u>Visc. Index</u>	175	175	169	172	169	171	174	173		151	172	170	179	172	178
<u>Viscosity 40°</u>		79.3	90	85	88	88.5	75	75.5	84	102	84.7	86.2	93.7	87.4	75.4
<u>Viscosity 100°</u>	15	13.5	14.2	14	14.3	14.5	13	13	14.0	14.8	14.1	14.2	15.7	14.4	13.1
<u>Viscosity -35°</u>			6400		<6600	<6600	5800	6200							
<u>Ht/Hs Visc150°</u>					3.5	>3.5					3.64	3.73	3.91		
<u>Pour point</u>	<-36°C	-33°C	-36°C	-39°C	-39°C	-42°C	-42°C	-42°C	-39°C	-45°C	-39°C	-36°C		-45°C	-39°C
<u>Flash point</u>	>200°C	200°C	210°	228°	230°C	230°C	202	203°C	222°C	226°C	234°C	230°C	218°C	242°C	217°C
<u>Density15/20°</u>	0.856	0.858	0.856	0.853	0.855	0.850	0.850	0.850	0.850	0.850	0.845	0.850		0.884	0.851
<u>TBN</u>	10.2	11.2	10.4		7.4	8.9				12	7.5	10.1			
<u>Sulfate ash</u>					0.8	1.2	0.8	0.8	1.1	1.35	0.8	1.09			